



Section 1: Identification of the Substance/Mixture and of the Company Undertaking

79300/79301

Product identifier used on the label:

Product Name: ADAPT Paste

Other means of identification:

Product Codes: 79300/79301

Manufacturer MSDS Number: 79300/79301

Recommended use of the chemical and restrictions on use:

Product Uses: This product is for external use, to be applied to the skin barrier that is used to attach an ostomy pouch to the skin. It fills any uneven wrinkles or crevices on the skin's surface to prevent leaks from the ostomy pouch and protects the skin around the stoma.

Product Restrictions: For external use only.
Caution: Contains alcohol. Do not apply to severely irritated or eroded skin, open cuts or sores. A temporary stinging sensation may occur if applied to irritated skin.

Chemical manufacturer address and telephone number:

Manufacturer Name: Hollister Incorporated

Manufacturer Address 1: 2000 Hollister Drive

Manufacturer City: Libertyville

Manufacturer State: Illinois

Manufacturer Zip Code: 60048

Manufacturer Country: USA

Manufacturer Web: www.Hollister.com

Business Phone: 847-680-1000

Emergency phone number:

Emergency Phone: 847-680-1000

Revision Date: 2018-12-17

Section 2: Hazards Identification

79300/79301

Classification of the chemical in accordance with CFR 1910.1200(d)(f):



Signal Words: Warning.

Emergency Overview: WARNING! Irritant.

Product:

GHS Class: Eye Irritation. Category 2.
Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3.

Hazard Statements: H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary Statements:

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301+P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P264 - Wash hands thoroughly after handling.
P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Section 3: Composition/Information on Ingredients

79300/79301

Mixtures:

Ingredient Name	CAS Number	Ingredient Percent	EC Number	Comments
ethanol	64-17-5	10 - 20% by weight		
butanol normal	71-36-3	10 - 20 % by weight		
butyl ester of polyvinylmethylether/maleic anhydride copolymer	54578-91-5	20 - 40% by weight		
Non-hazardous ingredient(s)	No data	20 - 40 % by weight		

Section 4: First Aid Measures

79300/79301

Description of necessary measures:

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact: No effects anticipated. If symptoms persist, call a physician.

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: IF SWALLOWED: Call a physician or poison control center immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed:

Indication of immediate medical attention and special treatment needed

Note To Physicians: None.

Section 5: Firefighting Measures

79300/79301

Suitable and unsuitable extinguishing media

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

Unsuitable Media: Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Hazardous Combustion Byproducts: Oxides of carbon, oxides of nitrogen and other organic substances may be formed.

Unusual Fire Hazards: Material burns with an invisible flame

Special protective equipment and precautions for fire-fighters

Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
NFPA Health:	1
NFPA Fire:	1
NFPA Reactivity:	1

Section 6: Accidental Release Measures

79300/79301

Personal precautions, protective equipment and emergency procedures

Personnel Precautions:	For large spills: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Avoid breathing vapor, aerosol or mist. Avoid contact with skin, eyes and clothing.
-------------------------------	--

Methods and materials for containment and cleaning up

Methods for Containment:	For large spills: Contain spills with an inert absorbent material such as soil, sand or oil dry.
Methods for Cleanup:	For large spills: Remove all sources of ignition. Collect the wipes with a non sparking tool and absorb or wipe any residual liquids. Place in a suitable container for proper disposal. Use appropriate protective apparel as described in Section 8. Avoid contact with skin and eyes.

Environmental precautions

Environmental Precautions:	For large spills: Avoid runoff into storm sewers, ditches, and waterways.
-----------------------------------	---

Section 7: Handling and Storage

79300/79301

Precautions for safe handling

Handling:	Use with adequate ventilation. Avoid breathing vapor and fumes. Use only in accordance with directions. To reduce potential for static discharge, bond and ground containers when transferring material.
Special Handling:	Do not re-use empty containers.
Hygiene Practices:	Wash thoroughly after handling. Avoid inhaling vapors, mists, or fumes.

Conditions for safe storage, including any incompatibilities

Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use. Keep away from aldehydes, halogenated organics, halogens, strong acids, strong oxidizers.
-----------------	---

Section 8: Exposure Controls/Personal Protection

79300/79301

Exposure Guidelines

Exposure Guidelines - Ingredient Based:

ethanol:

ACGIH: TLV-STEL: 1000 ppm

OSHA: PEL-TWA: 1000 ppm

butanol normal:

ACGIH: TLV-TWA: 20 ppm

OSHA:

PEL-TWA: 100 ppm

Appropriate engineering controls

Engineering Controls: No special protective equipment required under normal conditions of use. General ventilation is sufficient if this product is being used in a controlled medical setting (clinic, hospital, medical office) for its sole intended topical purpose.

Individual protection measures

Eye Protection: No special protective equipment required under normal conditions of use. If splashes are likely to occur, wear: Chemical splash goggles.

Face Protection: No special protective equipment required under normal conditions of use. If splashes are likely to occur, wear: Chemical splash goggles.

Skin Protection: No special protective equipment required under normal conditions of use.

Respiratory Protection: No special protective equipment required under normal conditions of use. No personal respiratory protective equipment is normally required. The need for respiratory protection will vary according to the airborne concentrations and environmental conditions (such as in manufacturing).

Hygiene Practices: Wash thoroughly after handling. Avoid inhaling vapors, mists, or fumes.

Section 9: Physical and Chemical Properties

79300/79301

Physical and chemical properties

Physical State: Physical State Appearance : Paste .

Color: Brown

Odor: Alcohol or solvent odor

pH: Not determined.

Melting Temperature: Not determined.

Boiling Temperature: 82°C (180 °F) as isopropanol

Flash Point: Combustion propagation rate less than or equal to 1 mm/s

Flash Point Method: ASTM Method D4359

Ignition Temperature: Not determined.

Lower Flammable Limit: Not determined.

Upper Flammable Limit: Not determined.

Decomposition Temperature: Not determined.

Vapor Pressure: 33 mm Hg @ 20°C (69°F) as isopropanol

Vapor Density: >1 (Air=1.)

Density: Not determined.

Solubility: SWELLS IN WATER

Specific Gravity: 1.075 at 25°C as mixture

Evaporation Rate: Not determined.

Percent Volatile: Not determined.

Viscosity: Not determined.

Odor Threshold: Not determined.

Octanol Water Partition Coef: Coefficient of Water/Oil Distribution: Not determined.

Auto Decomposition Temp: Not determined.

Section 10: Stability and Reactivity

79300/79301

Reactivity:**Chemical Stability:**

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions To Avoid: Keep away from heat, ignition sources and incompatible materials.

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

Hazardous Decomposition Products: Heating may produce an irritant and harmful gas.

Section 11: Toxicological Information

79300/79301

Toxicological Information:**Product:**

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Sign and Symptoms: Overexposure may cause headaches and dizziness.

Target Organ Data: Eyes. Skin. Respiratory system . Digestive system .

PreExisting Conditions Aggravated by Exposure: None generally recognized.

Acute Inhalation Effects: Prolonged or excessive inhalation may cause respiratory tract irritation.

Acute Skin Effects: May cause irritation.

Acute Ingestion Effects: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute Eye Effects: May cause irritation.

ethanol:**Eye Toxicity:**

Administration into the eye - Rabbit Standard Draize test: 500 mg [Severe]
Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild]
Administration into the eye - Rabbit Rinsed with water: 100 mg/4S [Moderate]
Administration into the eye - Rabbit Standard Draize test: 100 uL [Moderate] (RTECS)

Ingestion Toxicity:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 7060 mg/kg [Lungs, Thorax, or Respiration-Other changes]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 7 gm/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 15010 mg/kg [Behavioral-Somnolence (general depressed activity)Lungs, Thorax, or Respiration-Respiratory depressionGastrointestinal-Gastritis] (RTECS)

Inhalation Toxicity:

Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 20000 ppm/10H [Details of toxic effects not reported other than lethal dose value]
Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 5900 mg/m3/6H [Details of toxic effects not reported other than lethal dose value]
Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 124700 mg/m3/4H [Details of toxic effects not reported other than lethal dose value] (RTECS)

butanol normal:

Eye Toxicity:	Administration into the eye - Rabbit Standard Draize test: 2 mg/24H [Severe] Administration into the eye - Rabbit Standard Draize test: 1.62 mg [Severe] Administration into the eye - Rabbit Standard Draize test: 0.005 mL [Severe] (RTECS)
Skin Toxicity:	Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 3400 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion Toxicity:	Oral - Rat LD50 - Lethal dose, 50 percent kill: 790 mg/kg [Liver-Fatty liver degenerationKidney/Ureter/Bladder-Other changesBlood-Other changes] Oral - Rat LD50 - Lethal dose, 50 percent kill: 4.36 gm/kg [Gastrointestinal-GastritisLiver-Other changesBlood-Hemorrhage] Oral - Rat LD50 - Lethal dose, 50 percent kill: 0.79 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Inhalation Toxicity:	Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 24000 mg/m3/4H [Details of toxic effects not reported other than lethal dose value] Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: >8000 ppm/4H [Details of toxic effects not reported other than lethal dose value] (RTECS)

Section 12: Ecological Information

79300/79301

Ecotoxicity:

Product:

Ecotoxicity: No environmental information found for this product.

Persistence and degradability:

Product:

Environmental Fate: No environmental information found for this product.

Section 13: Disposal Considerations

79300/79301

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

Section 14: Transport Information

79300/79301

DOT Shipping Name:	Not applicable
DOT UN Number:	Not applicable
Notes from Section 14:	Not considered a dangerous good for shipping.

Section 15: Regulatory Information

79300/79301

Safety, health and environmental regulations specific for the product:

Regulatory - Ingredient Based:

ethanol:

Canada DSL: Listed

TSCA Inventory Status: Listed

butanol normal:

Canada DSL: Listed

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

butyl ester of polyvinylmethylether/maleic anhydride copolymer:

Canada DSL: Listed

TSCA Inventory Status: Listed

Section 16: Additional Information

79300/79301

Issue Date: 01/30/2015

Revision Date: 2018-12-17

Disclaimer: This product is exempt from Safety Data Sheet regulations as the product is for consumer use. The information contained in this Safety Data Sheet (SDS) is offered as a guide to the use and handling of this material. All safety aspects of all Hollister products are thoroughly evaluated prior to commercialization. This SDS has been prepared in good faith by technically knowledgeable personnel. Hollister Incorporated shall not be held liable for any damages, losses or injuries of any nature which may result from the use of or reliance upon any information contained in this SDS. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).

Copyright: Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

HMIS:

Health	1
Flammability	1
Reactivity	1
PPE	X

Chronic Health Hazard

NFPA:



Other Information:

Copyright © 1996-2018 Enviance Inc. All Rights Reserved.